


Data sheet

030M8T44

Joystick, 8-position, 8 Spring Return, 4 N.O.+4 N.C.



Features

Range	030 Command and Signalling EL-SG Ø 30
Product	Joysticks Ø 30
Type	8-position, spring return
Item code	030M8T44
Description	Joystick, 8-position, 8 Spring Return, 4 N.O.+4 N.C.
Colour	Black
Weight - gr	206,000
Custom tariff no.	85365080
GTIN	8052878029340

Technical data

Approvals	CE, (UL-CSA Microswitch only)
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-25° ÷ +65°C
Protection degree	IP65 (IEC-EN60529)
Mechanical durability	10.000.000 Operations
Cap or bellow material	Silicon rubber
Housing material	PA Polyamide
External bezel material	Chromed zinc alloy
Internal parts material	Lever and springs made in stainless steel AISI 304
Internal parts material	Sliding bushing made in brass
Microswitches flange material	Stainless steel AISI 304
Fixing diameter	30.5mm - Thickness 1÷6mm
Tightening torque	2 ÷ 3Nm (17.7 ÷ 26.6 Lb-in)
Rated insulation voltage	Ui 300V - Uimp 2.5KV (EN-IEC60947-1)
Overvoltage category	Class I (IEC-EN61140)
Microswitch contact form	SPDT (single pole double throw)
Microswitch terminals	Quick connect #250
Microswitch electrical ratings	250VAC - 16A (resistive load)
Microswitch electrical ratings	250VDC - 0.3A / 125VDC - 0.6A (resistive load)
Microswitch electrical durability	100.000 operations
Warranty period	18 months

Data sheet

030M8T44

Joystick, 8-position, 8 Spring Return, 4 N.O.+4 N.C.

Technical drawings

