


8740 C HF Zyklop bit socket with 1/2" drive with holding function, 6 x 140 mm

Zyklop Accessories, 1/2"



EAN:	4013288183507	Size:	206x44x22 mm
Part number:	05003842001	Weight:	86 g
Article number:	8740 C HF	Country of origin:	CZ
		Customs tariff number:	82079030

- Bit socket (non-impact) for manual or machine tool operations
- The holding function holds screws securely on the tool
- With Take it easy tool finder: colour coding by size
- Knurling on lower end for more grip when used manually.
- Chrome vanadium steel, matt chrome-plated

Bit socket with 1/2" drive and holding function for particularly comfortable screwdriving with reduced risk of losing the screw when feeding it into the workpiece. With "Take it easy" tool finder with colour coding by size - for quick and easy identification of the required tool .



Web link

https://products.wera.de/en/zyklop_ratchets_and_accessories_the_zyklop_ratchets_the_zyklop_ratchets_1_2_zyklop_accessories_1_2_8740_c_hf.html

Wera - 8740 C HF
05003842001 - 4013288183507

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Take it easy tool finder system



Take it easy tool finder system - with profile and size colour-coding for quick and easy tool selection. Colour-coded system for hexagon drive screws (L-Keys, Zyklop bit sockets), external hex drive screws and nuts (Joker wrenches, Zyklop sockets and Zyklop bit sockets with holding function), and TORX® drive screws (L-Keys, Zyklop bit sockets).

Manual and machine sockets



The manual and machine sockets can be used both for hand and power tools use (non-impact). Users need just one socket set for all applications.

Bit sockets with retaining function for hexagon socket screws



The clamping of the screw is achieved by a flexible locking ball. The holding function is especially helpful in confined, hard-to-reach spaces, where there is no room for a second hand to secure the screw.

Bit sockets with retaining function for hexagon socket screws



The clamping of the screw is achieved by a flexible locking ball. The holding function is especially helpful in confined, hard-to-reach spaces, where there is no room for a second hand to secure the screw.

Web link

https://products.wera.de/en/zyklop_ratchets_and_accessories_the_zyklop_ratchets_the_zyklop_ratchets_1_2_zyklop_accessories_1_2_8740_c_hf.html

Wera - 8740 C HF
05003842001 - 4013288183507

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Further versions in this product family:

					
	mm	mm	mm	mm	mm
05003820001	4.0	60.0	14.0	21.5	21.5
05003840001	4.0	140.0	14.0	21.5	101.5
05003821001	5.0	60.0	14.0	21.5	21.5
05003841001	5.0	140.0	14.0	21.5	101.5
05003822001	6.0	60.0	14.0	21.5	21.5
05003842001	6.0	140.0	14.0	21.5	101.5
05003823001	7.0	60.0	14.0	23.5	21.5
05003843001	7.0	140.0	14.0	23.5	101.5
05003824001	8.0	60.0	16.0	23.5	21.5
05003844001	8.0	140.0	16.0	23.5	101.5
05003825001	10.0	60.0	16.0	23.5	21.5
05003845001	10.0	140.0	16.0	23.5	101.5
05003826001	12.0	60.0	21.0	23.5	23.0
05003827001	14.0	60.0	22.0	23.5	23.0
05003828001	17.0	60.0	24.5	25.5	23.0
05003829001	19.0	60.0	26.5	27.5	23.0

Web link

https://products.wera.de/en/zyklop_ratchets_and_accessories_the_zyklop_ratchets_the_zyklop_ratchets_1_2_zyklop_accessories_1_2_8740_c_hf.html

Wera - 8740 C HF

05003842001 - 4013288183507

Wera Werkzeuge GmbH

Korzerter Straße 21-25

D-42349 Wuppertal

Tel: +49 (0)2 02 / 40 45-0

E-Mail: info@wera.de