KRAMP

TECHNICAL DATA SHEET

KRAMP
TRANSMISSION OIL 85W-140

LUBRICANT FOR GEARBOXES AND AXLES

APPLICATIONS

KRAMP TRANSMISSION OIL 85W-140 is a semi-synthetic extreme pressure oil recommended for lubricating gears subjected to high loads, equipping industrial vehicles, public works machinery and agricultural equipment, for which an API GL5 level lubricant is required.

ADVANTAGES

- Anti-wear and Extreme Pressure properties reinforced
- Compatibility with non-ferrous metals
- Good thermal stability
- Parts cleanliness
- Protection against high-temperature oxidation
- Excellent anti-foam properties

PERFORMANCES

API GL-5
VOITH 132.00374400
MIL-L2105 D
ZF TE-ML 05A, 07A, 08, 16C, 21A

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	AVERAGE VALUES
SAE grade	**-**	**-**	**SAE 85W-140**
Volume mass at 20°C	kg/m^3	NF T 60-101	896
Kinematic viscosity at 40°C	mm²/s	NF T 60-100	384
Kinematic viscosity at 100°C	mm²/s	NF T 60-100	27.0
Viscosity index	-	NF T 60-136	96
Flash point	°C	NF T 60-118	200
Pour point	°C	NF T 60-105	-24
Brookfield viscosity at -12°C	mPa.s	NF T 60-152	112 500

The average characteristics are given for information only

HEALTH, SAFETY AND ENVIRONMENT

Disposal methods must comply with current applicable regulations concerning the disposal of waste oils.
Store in a sheltered area.