

Kramp Acrylic Spray Paint (Aerosols)

2025/01

Product description

Kramp Acrylic-Spray is a premium quality acrylic paint available in different colour shades e. g. in accordance to RAL-Norm.

Colour matched spraying and repair work in specific colour shades.

Especially suited for the spot repair of machines, machinery parts, tools, vehicles, and much more.

Characteristics

- Fast drying
- High coverage and opacity
- Lightfast and non-yellowing
- Durable surface hardness
- Scratch and shock resistant.
- Highly pigmented 1K acrylic quality

Substrate

Fully hardened and sanded old paint work, thoroughly dry 1K- and 2K-filler materials.

Pretreatment / Cleansing:

Pre-cleansing with Kramp Silicone Remover

Colours / Grade of Gloss

Various RAL-colours and gloss levels

Preparation:

Shake can vigorously until the mixing balls move freely!

Application:

Spray to test - Spraying distance approx. 20 - 30 cm

2 - 3 coats, dry film thickness 30 - 40 µm.

Flash-off:

3 - 5 min. between each coating

After use:

Turn can upside down and spray until the valve is clean, this prevents the valve from clogging up.

Drying

Dust dry: 5 - 10 min.

Set to touch: 20 - 30 min.

Full hardness: 24 h



Processing

Conditions: From +10°C and up to 80% relative air humidity

Storage: In tightly closed original containers at least 2 years shelf life

VOC-Regulation: This product contains max. 700 g/l VOC (5.84 lbs/gal)

Safety Information: Read the corresponding Material Safety Data Sheet

Kramp GmbH
Meieriedstrasse 4A
CH-3400 Burgdorf
+41 (0)34 420 84 44

Kramp UK Ltd
Unit 5, Lancaster Way
SG18 8YL Biggleswade
+44 (0)1767 602615

Kramp Groep B.V.
Breukelaarweg 33
NL-7051 DW Varsseveld
+31 (0)315 254 299

www.kramp.com

KRAMP
It's that easy.