



Mechanical nozzle valve

AdBlue®/DEF-G 1" female-60 l/min-PP

Item number: 23 163 878
EAN: 4048358709769
Discount group: D

Technical data

Connection: G 1" male with hose fitting, NW 19 mm / 0.75 inch
Flow capacity max. (l/min) / (gpm): 60 / 15
Outside diameter discharge tube (mm) / (inch): 18 / 0.7
Switch-off: manual
Working pressure (bar) / (psi): 0,5 - 4 / 7.3 - 58
Operating pressure max. (bar/psi): 4 / 58

Materials of parts in contact with liquid

Casing: Plastic
Discharge: Stainless steel
Piston: POM
Pressure spring: Stainless steel
Seals: FKM
Nipple: PA 6 GF 30
Union nut: PA 6 GF 30
Cap: Plastic

Dimensions LxWxH (mm) / (inch): 330 x 170 x 50 / 12.99 x 6.69 x 1.97
Weight (kg) / (lb): 0,53 / 1.17

Specification

- Mechanical control nozzle for AdBlue®
- Note in the case of the formation of crystals: To dissolve the crystals, bring the AdBlue® nozzle in the compressed (open) position and put it in hot water for half an hour (max. 50 °C / 122 °F)

Packaging

Dimensions LxWxH (mm) / (inch): 400 x 170 x 60 / 15.75 x 6.69 x 2.36
Weight including package (kg) / (lb): 0,53 / 1.17
Packing unit: 1,0