

# 3M™ PELTOR™ WS™ ALERT™ XP Headset

## Hearing protection with Bluetooth® Technology

### **Product Description**

The 3M™ PELTOR™ WS™ ALERT™ XP Headset is the next generation protective communication solution. With Bluetooth® wireless communication, noise-cancelling boom microphone, integrated FM-Radio and level-dependent function for ambient listening, the WS™ ALERT™ XP Headset not only helps protect you against hazardous noise, but also makes it easy to make phone calls with both hands free in noisy environments.

### **Key Features**

- High attenuating hearing protector in two models: stand-alone headband or safety helmet attachment (SNR 30 dB)
- Bluetooth® Technology for connection to one external device for hands-free talk and streaming
- Noise cancelling boom microphone for clear speech transmission in noisy environments
- Level-dependent function for ambient listening to help improve your situational awareness
- Auto-pairing to quickly pair and connect to your mobile device
- Built-in FM-Radio with radio volume limited to 82dB
- Voice guided menu system
- Digital station search with ability to store up to 4 favorite stations
- Auto power off: The headset will turn off after 4 hrs of non-use to save battery
- Low-battery warning at low battery level
- To reduce the corrosion caused by sweat, the electronics are located in the outer part of the cup
- Rechargeable option with NiMH batteries
- · Replaceable cushions and foam liners

### **Applications**

The 3M™ PELTOR™ WS™ ALERT™ XP Headset offers Bluetooth® wireless communication in noisy environments or in and out of noise. Useful when users need to be connected to their mobile phone throughout the day (e.g. handymen in construction companies, private contractors driving their own machines, farmers in agriculture business, maintenance workers in industrial applications etc.); everywhere hands-free communication and hearing protection could be of benefit.

### **Standards and Approvals**

Hereby, 3M Svenska AB declares that the radio equipment type Radio broadcast receiver is in compliance with Directive 2014/53/EU and other appropriate directives to fulfill the requirements for the CE marking. The full text of the EU declaration of conformity is available at the following internet address: www.3M. com/PELTOR/DOC. A copy of the declaration of conformity and additional information required in the directives can also be obtained by contacting 3M in the country of purchase. For contact information, see last pages of the user instruction. The product has been tested and approved in accordance with EN 352-1:2002, EN 352-3:2002, EN 352-4:2001/A1:2005, EN 352-6:2002, EN 352-8:2008. Notified Body Statement of Opinion offered by: FIOH, Finnish Institute of Occupational Health, Topeliuksenkatu 41 b, FI-00250, Helsinki, Finland. Notified body #0403.



MRX21A2WS6



MRX21P3E2WS6



Bluetooth® technology for connection to one external device for hands-free talk and streaming



Noise cancelling boom microphone for clear speech transmission in noisy environments



Level-dependent function for ambient listening



Built-in FM-radio

### **Headset Models and Accessories**

Article number	Description	3M ID	SAPID
MRX21A2WS6	3M™ PELTOR™ WS™ ALERT™ XP Headset, headband, black	UU009153337	7100146915
MRX21P3E2WS6	3M™ PELTOR™ WS™ ALERT™ XP Headset, helmet attachment, black	UU009161132	7100147224
MRX21A2WS6-ACK	3M™ PELTOR™ WS™ ALERT™ XP Headset, incl. ACK (FR09,FR08, LR6NM), headband, black	UU009161124	7100147222
MRX21P3E2WS6-ACK	3M™ PELTOR™ WS™ ALERT™ XP Headset, incl. ACK (FR09,FR08, LR6NM), helmet attachment, black	UU009160928	7100147261
Article number	Description	3M ID	SAPID
HY82	3M™ PELTOR™ HY82 Hygiene kit	UU008567388	7100122439
FR08	3M™ PELTOR™ FR08 Power supply with USB connector	XH001680194	7000108521
FR09	3M™ PELTOR™ FR09 Battery charger with USB connector	XH001680616	7100075611
LR6NM	3M™ PELTOR™ LR6NM Rechargeable AA batteries, 2 ea	XH001659693	7100064688
M995/2	3M™ PELTOR™ M995 Wind shield for speech microphone, 2 ea	XH001679154	7010044372
HY100A	3M™ PELTOR™ HY100A Clean Hygiene Pad, 100pcs	XH001651351	7100064410
HYM1000	3M™ PELTOR™ HYM1000 Microphone protection, 5 meters	XH001651328	7100064281

# rev.a

### **Technical data specifications**

Materials: **Headband MRX21A2WS6** 

Headband: PVC, PA

Headband wire: stainless steel Two-point fastener: POM Cushion: PVC foil and PUR foam

Foam liner: PUR foam

Cup: ABS

Level-dependent microphone for ambient listening: PUR foam

Wind shield for speech microphone: ABS, PA

Antenna: PE, ABS, TPE Wind Shield: foam Charger jack: stainless steel

Helmet attachment/Hardhat MRX21P3E2WS6

Cup supporting arm: stainless steel

**Battery type:** 2xAA batteries (Alkaline)

Operating time: Approximately 58 hours (FM radio and level-dependent)

Approximately 78 hours (Bluetooth® streaming and level-dependent)

Weight (batteries incl.): MRX21A2WS6 (headband): 411 g

MRX21P3E2WS6 (helmet attachment): 431 g

Bluetooth® Technology: Bluetooth version: 4.2

> Bluetooth headset profile (HSP): 1.2 Bluetooth hands-free profile (HFP): 1.6

Bluetooth Advanced Audio Distribution Profile (A2DP): 1.3

Audio/Video Remote Control Profile (AVRCP): 1.6

Bluetooth Range: Up to 10m (class 2)

27 mm diameter, 100 Ohm Speakers:

Noise cancelling electret microphone Boom microphone type: -20°C to +55°C (battery dependent) Operating temperature:

-20°C to +55°C Storage temperature:

**Shelf life:** 5 years excl. batteries

Use limitation: Never modify or alter this product

### **Attenuation Europe**

### MRX21A2WS6\*

### EN352-1:2002

Frequency (Hz) f	125	250	500	1000	2000	4000	8000	SNR
Mean Attenuation M <sub>f</sub> (dB)	13.8	19.3	30.4	34.5	37.7	39.5	36.2	
Standard deviation $s_f$ (dB)	2.7	2.4	2.7	3.6	2.3	2.7	4.1	30
Assumed Protection Value APV <sub>f</sub> (dB)	11.1	16.9	27.7	30.9	35.4	36.8	32.1	



H=35 dB M=27 dB L=18 dB

### MRX21P3F2WS6\*

### EN352-3:2002

Frequency (Hz) f	125	250	500	1000	2000	4000	8000	SNR
Mean Attenuation $M_f$ (dB)	14.2	19.7	29.6	33.4	36.3	39.5	34.6	
Standard deviation $s_f(dB)$	3.9	1.9	2.5	1.8	2.5	2.7	4.9	30
Assumed Protection Value $APV_f$ (dB)	10.3	17.8	27.1	31.6	33.8	36.8	29.7	



H=34 dB M=27 dB L=18 dB

The SNR may overestimate the hearing protection provided during typical use. 3M recommends reducing the SNR by 50% for estimating the amount of noise reduction provided.

### In the box (MRX21\*2WS6)

1x Headset

2 x AA batteries

1x User Instruction

In the box (MRX21\*2WS6-ACK)

2 x NiMH rechargeable AA batteries (LR6NM)

1x Battery charger with USB connector (FRO9)

1x Power supply with USB connector (FR08)

1x User Instruction



### 3M Personal Safety Division

3M Svenska AB, Box 2341 SE-331 02 Värnamo Sweden

Internet: www.3M.com/PELTOR E-mail: cstechservice@mmm.com Phone: +46 370 65 65 00

Please recycle. Printed in Sweden. © 3M 2018. All rights reserved.

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by 3M Company is under license. 3M, WS and ALERT are trademarks of 3M Company, used under license in Canada. PELTOR is a trademark of 3M Svenska AB, used under license in Canada.

The warranty does not cover any damage caused by neglected maintenance or

For more information on maintenance, please see the user instruction.

For complete warranty condition, contact your dealer or local 3M office.

Important Notice
3M does not accept liability of any kind, be it direct or consequential (including, but not limited to, loss of profits, business and/or goodwill) arising from reliance upon any information herein provided by 3M.

The user is responsible for determining the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict

3M's liability for death or personal injury arising from its negligence.