



COMPRESSOR OIL ISO 46

LUBRICANT FOR ROTARY AIR COMPRESSORS

APPLICATIONS

COMPRESSOR OIL ISO 46 are formulated based mineral oil recommended for the lubrication of screw or paddle rotary air compressors.

PROPERTIES

- Slight tendency to form deposits
- Exceptional resistance to oxidation
- Low volatility
- Excellent anti-wear and anti-corrosion properties
-

PERFORMANCE LEVELS

ISO 6743-3 A DAG/DAH

CHARACTERISTICS

CHARACTERISTICS	UNITS	METHODS	TYPICAL DATA
Grade ISO	-	-	46
Volume mass at 15°C	kg/m ³	NF T 60-101	876
Kinematic viscosity at 40°C	mm ² /s	NF T 60-100	47
Kinematic viscosity at 100°C	mm ² /s	NF T 60-100	7
Viscosity index	-	NF T 60-136	102
Flash point	°C	NF T 60-118	230
Pour point	°C	NF T 60-105	-30

This typical data is given for information only.

HEALTH, SAFETY AND ENVIRONMENT

Disposal methods must comply with current applicable regulations concerning the disposal of waste oils.

Must be stored away from bad weather.

Our technical department is at your disposal to provide the advice you need.