

TECHNICAL DATASHEET

519000011

Rev.00



FEATURES:

- Overmoulded terminal for better comfort and stability
- Side venting
- Adjustment of temples in length and inclination
- Can be worn over prescription glasses

FRAME FEATURES:

Frame Typology	Spectacle
PPE field of view	>40
Temple adjustment	Inclination and Length
Weight (g)	43
Size (mm)	136 116-129
Material Features	Anallergic

FEATURES OCULARS/LENSES:

Ocular/Flip-up Material	Polycarbonate
Colour	Clear
Technical Treatment	Antifog PLUS Antiscratch PLUS
Aesthetic Treatment	-
Thickness [mm](+/- 0.1)	2
Curvature	Base 3 Spheric
Optical Class	1
UV Protection	380 nm
Spare Parts	-
VLT% (+/-5%)	91,2

MARKING DATA:

Standard References	EN166 EN170
Frame Marking	Mod.519 U EN166 FT CE U EN175 FT CE
Ocular/Flip-up Marking	2C-1.2 U 1 FT K N CE

APPLICATION FIELDS

Protection against high-speed particles 45 m/s - low energy (F); Protection against high-speed particles at extreme temperatures (T); Resistance to fogging of oculars (N); Resistance to surface damage by fine particles (K)

Notes

