



| | | | | |
|---|--------|--|---|---------------------------------|
| Engine model Type de moteur Modelo de motor | 6T-590 | Build prefix Code constructeur Código de constructor | - | Turbo charged Turbo Turbo |
|---|--------|--|---|---------------------------------|








| |
|--|
| Cylinder bore Alésage du cylindre Calibre del cilindro |
| 102mm |

| |
|---|
| Piston stroke Course du piston Recorrido del pistón |
| 120mm |

| |
|---|
| Engine capacity Cylindrée Capacidad del motor |
| 5.8 litre |

| |
|---|
| Number of cylinders Nombre de cylindres Número de cilindros |
| 6 |

Specifications / Spécifications / Especificaciones

| | | | | | | | |
|---|---|---|---|--|---|---|-------------|
|  |  |  |  |  |  |  | |
| A (mm) | B (mm) | C (mm) | | D (mm) | E (mm) | F (mm) | G (mm) |
| 0.25 | 0.5 | 1 | 0.99 - 1.52 | 0 | | 1 | 0.30 - 0.51 |
| | | 2 | 0.99 - 1.52 | | | 2 | - |

Torque specifications / Spécifications de couple / Especificación de torsión

| | | Nm | lbft | Degrees |
|--|---|-----|------|---------|
| Cylinder head bolts Vis de culasse Pernos culata | 1st stage (a) 1ère étape (a) Primer paso (a) | 41 | 30 | |
| | 2nd stage (a) 2ème étape (a) Segundo paso (a) | 90 | 66 | |
| | 3rd stage (b) 3ème étape (b) Tercer paso (b) | 217 | 160 | |
| | 4th stage (a) 4ème étape (a) Cuarto paso (a) | | | 90 |
| Main bearing bolts Vis, chaise de palier-vilebrequin Pernos rodamiento principal | | 197 | 145 | |
| Connecting rod bolts Vis de bielles Pernos de biela | | 149 | 110 | |
| Flywheel bolts Boulons de roue Pernos volante | | 197 | 145 | |

a - All bolts / Tous les boulons / Todos los pernos

b - Long bolts only / Longs boulons seulement / Tornillos largos sol