



- Multi-functional electronic starter, power supply unit and tester with Li-ion lithium battery for 12/24V cranking (12000A start max). With LCD display.
- OVER RIDE function for cranking in emergency conditions with no battery or completely flat.
- SUPPLY function for stable power supply during battery changes.
- Battery TEST function (cranking efficiency/charge status) and alternator.
- High efficiency led for use as emergency light.

TECHNICAL DATA

CODE	829528	STARTING VOLTAGE	12 / 24 V	DIMENSIONS (LxWxH)	15,5x23,4x31,8cm
CHARGE MAINS VOLTAGE 1ph	100 - 240 V	MAX STARTING CURRENT	12000 / 6000 A	WEIGHT	4,580 kg
CHARGE MAINS FREQUENCY	50 / 60 Hz	.	225 / 200 Ah		
BATTERY CAPACITY	40000 mAh	PROTECTION DEGREE	IP43		

SUPPLIED ACCESSORIES

169999 MULTI PLUG POWER SUPPLY

DESCRIPTION

Multifunction electronic starter, power supply and tester, with Li-ion lithium battery for 12V/24V starting of cars, vans, small boats, lorries etc.

It performs control tests on the battery: voltage at terminals, starting capacity (CCA) and operational check of the vehicle alternator.

The OVER RIDE function allows starting in emergency conditions when battery is missing (or completely down).

It is a stable and reliable power supply source for battery charges (SUPPLY function).

Robust and compact, it is equipped with high intensity LED light.

Protection against: polarity reversal, short-circuit, overvoltage (incompatible battery voltage), undervoltage (cut-off voltage), overcurrent, overheating, under-temperature, accidental contacts, alternator return currents.

Complete with starting cables and wall charge.

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SPARE PARTS LIST



BROCHURE



CERTIFICATE