

// LIQUID FOOD



// 49200

General purpose food quality - PVC FDA - EU 10/2011 A+B+C+D1

Tube: transparent PVC.

Reinforcement: high tensile textile cords.

Cover: transparent PVC with longitudinal red stripes - abrasion and ozone resistant.

Application: general purpose food quality.

Clean with 5% soda solution - see Alfagomma hose cleaning guidelines.

Temperature: -5 °C +60 °C (+23 °F +140 °F)

ID (mm)	ID (in)	OD (mm)	OD (in)	WP (bar)	WP (psi)	BP (bar)	BP (psi)	Weight (kg/m)	Weight (lb/ ft)
6,0	1/4"	11,0	0,43	20	300	60	900	0,085	0,06
6,0	1/4"	12,0	0,47	20	300	60	900	0,110	0,08
8,0	5/16"	13,0	0,51	15	225	45	650	0,105	0,08
8,0	5/16"	14,0	0,55	15	225	45	650	0,130	0,09
10,0	3/8"	15,0	0,59	15	225	45	650	0,125	0,09
10,0	3/8"	16,0	0,63	15	225	45	650	0,155	0,11
13,0	1/2"	19,0	0,75	10	150	30	450	0,190	0,13
16,0	5/8"	22,0	0,87	10	150	30	450	0,225	0,16
19,0	3/4"	25,0	0,98	10	150	30	450	0,260	0,18
19,0	3/4"	26,0	1,02	10	150	30	450	0,310	0,21
25,0	1"	32,0	1,26	10	150	30	450	0,390	0,27
25,0	1"	33,0	1,30	10	150	30	450	0,450	0,31
30,0	1 3/16"	38,0	1,50	7	100	21	300	0,530	0,36
32,0	1 1/4"	42,0	1,65	7	100	21	300	0,715	0,49
38,0	1 1/2"	48,0	1,89	7	100	21	300	0,830	0,56
51,0	2"	63,0	2,48	6	90	18	270	1,330	0,90