

Product information

95 16 200

Cable Shears

With twin cutting edge

IEC 60900 DIN EN 60900

- For cutting copper and aluminium cables
- Not suitable for steel wire and hard drawn copper conductors
- Precision-ground, hardened blades
- Clean and smooth cut without crushing and deformation
- Adjustable bolted joint, self-retaining screw
- Low handforce required due to favourable lever ratio and special blade geometry
- Pinch guard prevents operators' fingers being pinched
- High-grade special tool steel, forged, oil-hardened



▲ 1000 V

General

Article No.	95 16 200
EAN	4003773026761
Shears	chrome-plated
Handles	insulated with multi-component grips, VDE-tested
Weight	340 g
Dimensions	200 x 68 x 19 mm
Standard	DIN EN 60900 IEC 60900
REACH compliant	does not contain SVHC
RoHS compliant	not applicable

Technical details

Cutting capacity copper cable, multiple-stranded	70 mm ²
Cutting capacity copper cable, multiple-stranded	Ø 20 mm
AWG	2 / 0
VDE tested	yes

technical change and errors excepted



Final cut: after cutting the sheath in the front profile the conductors in the rear part are cut. Initial cut in the front profile, final cut in the rear profile - to keep it as easy as possible.



Initial cut: using the front cutting edge to cut the insulating sheath on larger cable diameters leaves an ergonomic handle opening width.