

# Kramp Aluminium grease      AG02400KR

Kramp Aluminium grease is a special lubricant for gears, ropes and chains. The aluminium-based antifriction spray is a product used for high temperature and extreme pressure that allows excellent results on a large scale of temperatures ranging from -185 ° to + 450 ° C in the atmosphere. In hydrogen reaches 700 °C and in inert atmosphere or vacuum we found up to 1000 °C. Antifriction, anti-blocking, high temperatures and extreme pressure lubricant. The product is used on surfaces to be treated as a self-lubricating and anti-corrosive film. This grease is resistant to extreme pressure, it eliminates friction between metals, it is durable and has a good penetration power.

## Application:

- Recommended in all the above mentioned situations.
- Used also on: open gears, wire ropes, cables and chains that need lubrication and permanent protection, i.e. machines for ground handling, cranes, excavators, machines for the construction industry, mixers, tape and cable conveyors, hoists, lifts, fork lifts, mixers, industrial oven chains and ropes, etc.

## Health- and Safety Recommendations:

Use only in well-ventilated areas.

In case of contact with eyes, wash immediately with plenty of water.

Not subject to Biodegradation

Flammable

Avoid contact with eyes and skin

## Packaging & logistics

Shelf life: 2 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C

Packaging: 400 ml aerosol

### Technical datasheet

**Kramp Aluminium grease**

**Revision: 21-05-2025**

This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. It is general in nature and does not constitute any liability. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application. In every case it is recommended to carry out preliminary experiments. The manufacturer reserves the right to modify products without prior notice.