

# ABMESSUNGSTABELLE

| DN Futterrohr/<br>Kernbohrung [mm] | für Rohr-Ø<br>[mm] | Gliederanzahl x<br>Modul-Typ |
|------------------------------------|--------------------|------------------------------|
| 80                                 | 42 + 48            | 5 x 265                      |
| 100                                | 34 + 42            | 5 x 340                      |
|                                    | 48                 | 6 x 315                      |
|                                    | 58 + 60            | 6 x 300                      |
| 125                                | 42 + 48 + 58       | 5 x 360                      |
|                                    | 60                 | 7 x 340                      |
|                                    | 76 + 78            | 8 x 315                      |
| 150                                | 58 + 60            | 5 x 410                      |
|                                    | 76                 | 6 x 360                      |
|                                    | 83                 | 7 x 360                      |
|                                    | 89                 | 9 x 340                      |
|                                    | 98                 | 10 x 315                     |
|                                    | 110                | 7 x 310                      |
|                                    | 114                | 10 x 265                     |
| 200                                | 110                | 7 x 475                      |
|                                    | 114                | 7 x 410                      |
|                                    | 135                | 13 x 340                     |

| DN Futterrohr/<br>Kernbohrung [mm] | für Rohr-Ø<br>[mm] | Gliederanzahl x<br>Modul-Typ |
|------------------------------------|--------------------|------------------------------|
| 250                                | 160                | 9 x 475                      |
|                                    | 168                | 7 x 400                      |
| 300                                | 160 + 168 +<br>170 | 7 x 500                      |
|                                    | 210 + 219          | 12 x 410                     |
|                                    | 222                | 15 x 360                     |
| 350                                | 273                | 18 x 360                     |
| 400                                | 324                | 21 x 360                     |
| 500                                | 406                | 21 x 475                     |
|                                    | 429                | 16 x 425                     |
| 600                                | 508                | 25 x 475                     |
|                                    | 532                | 19 x 425                     |
| 700                                | 610                | 30 x 475                     |
| 800                                | 711                | 25 x 400                     |
| 900                                | 813                | 39 x 475                     |
| 1000                               | 914                | 32 x 400                     |

| Modul-Typ | Erforderliche<br>Mauerdicke |
|-----------|-----------------------------|
| LS 200    | 75 mm                       |
| LS 265    |                             |
| LS 275    |                             |
| LS 300    | 100 mm                      |
| LS 310    |                             |
| LS 315    |                             |
| LS 325    | 120 mm                      |
| LS 340    |                             |
| LS 360    |                             |
| LS 400    | 140 mm                      |

| Modul-Typ | Erforderliche<br>Mauerdicke |
|-----------|-----------------------------|
| LS 410    | 140 mm                      |
| LS 425    |                             |
| LS 440    |                             |
| LS 475    |                             |
| LS 500    | 150 mm                      |
| LS 525    |                             |
| LS 575    |                             |
| LS 625    |                             |
| LS 700    |                             |

| Link Seal Modul-Typ | Ausführung C, S 316 |
|---------------------|---------------------|
| LS 200 bis LS 275   | 2 Nm                |
| LS 300 bis LS 360   | 8 Nm                |
| LS 400 bis LS 475   | 27 Nm               |
| LS 500 bis LS 575   | 65 Nm               |
| LS 615              | 110 Nm              |
| LS 625 bis LS 700   | 65 Nm               |

Maximale Drehmomente