



Basic features

| | |
|---------------------|----------------------------|
| Approval/Conformity | cULus CE EAC WEEE |
| Basic standard | IEC 60947-5-2 |
| Trademark | Global |

Display/Operation

| | |
|--------------------|-----|
| Function indicator | yes |
| Power indicator | no |

Electrical connection

| | |
|-----------------------------------|----------------------|
| Cable diameter D | 4.60 mm |
| Cable length L | 2 m |
| Conductor cross-section | 0.34 mm ² |
| Connection type | Cable, 2.00 m, PVC |
| Number of conductors | 2 |
| Polarity reversal protected | yes |
| Protection against device mix-ups | yes |
| Short-circuit protection | yes |

Electrical data

| | |
|---|-------------|
| Load capacitance max. at U _e | 1 µF |
| Min. operating current I _m | 5 mA |
| Operating voltage U _b | 10...36 VDC |
| Rated insulation voltage U _i | 75 V DC |
| Rated operating current I _e | 100 mA |
| Rated operating voltage U _e DC | 24 V |
| Rated short circuit current | 100 A |
| Ready delay t _v max. | 50 ms |
| Residual current I _r max. | 600 µA |
| Ripple max. (% of U _e) | 15 % |
| Switching frequency | 600 Hz |
| Utilization category | DC -13 |
| Voltage drop static max. | 4.2 V |

Environmental conditions

| | |
|-------------------------|---------------------------------------|
| Ambient temperature | -25...70 °C |
| Contamination scale | 3 |
| EN 60068-2-27, Shock | Half-sinus, 30 g _n , 11 ms |
| EN 60068-2-6, Vibration | 55 Hz, amplitude 1 mm, 3x30 min |
| IP rating | IP67 |

Functional safety

| | |
|--------------|-------|
| MTTF (40 °C) | 315 a |
|--------------|-------|

Material

| | |
|--------------------------|---------------------------|
| Housing material | Brass, Nickel-free coated |
| Jacket material | PVC |
| Material sensing surface | PA 12 |

Inductive Sensors
BES M18MG-GSC70B-BV02
Order Code: BES00FA

BALLUFF

Mechanical data

| | |
|-------------------|--------------------|
| Dimension | Ø 18 x 46 mm |
| Installation | for flush mounting |
| Size | M18x1 |
| Tightening torque | 25 Nm |

Output/Interface

| | |
|------------------|------------------------------|
| Switching output | polarized normally open (NO) |
|------------------|------------------------------|

Range/Distance

| | |
|----------------------------------|--------|
| Assured operating distance Sa | 5.6 mm |
| Hysteresis H max. (% of Sr) | 20.0 % |
| Rated operating distance Sn | 7 mm |
| Real switching distance sr | 7 mm |
| Repeat accuracy max. (% of Sr) | 5.0 % |
| Switching distance marking | ■ ■ |
| Temperature drift max. (% of Sr) | 10 % |
| Tolerance Sr | ±10 % |

Remarks

Specify maximum attainable switching frequency (not per IEC 60947-5-2)

Flush: See installation instructions for inductive sensors with extended range 825357.

The sensor is functional again after the overload has been eliminated.

For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Wiring Diagrams

