

Kramp Contact spray

CO02500KR

Kramp Contact spray is a universal spray for the cleaning and maintenance of electric contact areas.

Properties:

- Rust and corrosion-resistant
- Improves transmission
- Prevents loss of tension
- Reduces humidity
- Non corrosive
- Water-repellent
- In and outdoor use
- Aerosol can be used in any angle (360°)

Application:

- Suitable for electric contact points such as switches, stop contacts, batteries, measuring tools, etc.
- Cleans and deoxidizes surfaces and improves the power transmission at electric contacts.
- Prevents moisture penetration which could result in disturbances. Also suitable for dehumidising of electric wirework and tools.
- Ideal for electric installations, appliances, stop contacts and light switches....
-

Base	Mixture based on mineral oil
Consistency	Liquid
Density	Ca. 0,81 g/ml
Application temperature	+5°C → +35°C
Temperature resistance	-50°C → +190°C
Volatile organic component (VOC)	84 %
Viscosity	1 mPa.s
Acidity level	Neutral
Flashpoint	52°C
Solubility in water	Not soluble

Substrates:

- Substrate types: All types of metals and plastics.

Kramp Groep B.V.

Breukelaarweg 33
7051 DW Varsseveld

P.O. Box 73, 7050 AB Varsseveld

T +31 (0)315 - 254 299

F +31 (0)315 - 254 399

I www.kramp.com

IBAN BE26734044195229

SWIFT/BIC KREDEB33

VAT NL005435511B09

KvK 09219396

Application method:

Shake can well before use. Switch off electrical equipment before spraying the product.
Switch electric installations back on when spray is evaporated.

Health- and Safety Recommendations:

Dangerous. Respect the precautions for use.
Use only in well-ventilated areas.
In case of contact with eyes, wash immediately with plenty of water.

Packaging & logistics

Colour: Transparent
Packaging: 500 ml aerosol
Shelf life: 3 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C

Technical datasheet

Kramp Contact Spray Master Code: 9900127
Revision: 16-04-2025

This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. It is general in nature and does not constitute any liability. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application. In every case it is recommended to carry out preliminary experiments. The manufacturer reserves the right to modify products without prior notice.

Kramp Groep B.V.

Breukelaarweg 33
7051 DW Varsseveld
P.O. Box 73, 7050 AB Varsseveld

T +31 (0)315 - 254 299
F +31 (0)315 - 254 399
I www.kramp.com

IBAN BE26734044195229
SWIFT/BIC KREDBEBB
VAT NL005435511B09
KvK 09219396