

Receiver
From

Society
Reference
Address
Phone
Fax
E-mail

Item n° :

102660080

Model :

JET 92 M

Pump data

Pressure rating : 6 bar (600 kPa)
Min. fluid temperature : 0 °C
Max. fluid temperature : 35 °C
Max. Ambient temperature : 40 °C

Priming capacity :

H m	2	3	4	5	6	7	8	9
Q m³/h	4.8	4.32	3.96	3.66	3.36	3	2.46	1.86

Requested data



Flow : 0.00 m³/h
Head : 0.00 m
Fluid : Water, pure
Fluid Temperature : 20 °C
Density : 998.3 kg/m³
Kinematic viscosity : 1.005 mm²/s
Vapor pressure : 100.00 kPa

Hydraulic data (duty point)

Flow :
Head :

Materials

Pump body	Cast iron 200 UNI ISO 185
Support	Die cast aluminium
Impeller	Technopoly mer A
Mechanical seal	Carbon/Ceramic
OR ring	NBR Rubber
Shaft with rotor	AISI 416 X12 CrS 13 UNI 6900/71
Nozzle venturi diffuser assembly	Technopoly mer A

Curve tolerance according to ISO 9906

Motor data

Motor brand : DAB
Nominal power P2 : 0.75 kW
Rated speed : 2800 rpm
Rated voltage : 1~ 220-240 V 50 Hz
Nominal current : 4.2 A
Degree of protection : IP 44

Dimensions in
mm

A	395	DNA	1" G	G	111
A1	390	DNM	1" G	H	193
B	178	E	192	H3	144
C	108	F	14	I Ø	9

Weight : 11.7 kg

Pump connection

Suction side : 1 " G / 6 bar (600 kPa)
Discharge side : 1 " G / 6 bar (600 kPa)


Receiver

From

Society
Reference
Address
Phone
Fax
E-mail

JET 92 M

Curve tolerance according to ISO 9906




Hydraulic data (duty point)

Suction side : 1 " G 6 bar (600 kPa)	Discharge side : 1 " G 6 bar (600 kPa)	Flow : 0 m³/h	Head : 0 m	Rated speed : 2800 rpm
Project	Project ID	Created by	Created on 24/03/2016	

Society
Reference
Address
Phone
Fax
E-mail

JET 92 M



Dimensions in mm

1	A	395	H3	144					
2	A1	390	I Ø	9					
3	B	178							
4	C	108							
5	DNA	1" G							
6	DNM	1" G							
7	E	192							
8	F	14							
9	G	111							
10	H	193							

Pump connection

Suction
1 " G
6 bar (600 kPa)

Discharge
1 " G
6 bar (600 kPa)

Project

Project ID

Created by

Created on

24/03/2016