

## Product Image



/publicpictures/Produktbild/1151480020.tiff

## Master data

|                           |                       |
|---------------------------|-----------------------|
| Product number:           | 1151480020            |
| EAN:                      | 4007123688739         |
| Article owner:            | Brennenstuhl Tübingen |
| manufacturer:             | Brennenstuhl          |
| Product line:             |                       |
| Customised:               | No                    |
| Minimal care:             | No                    |
| Rejection indicator:      | J                     |
| Gewählte Vertriebsregion: | De                    |
| Gewählte Sprache:         | en                    |

## Texts

### IS4 designation 1/2:

Stromverteiler BSV P 1xCEE400V/16A 1xCEE230V, 3xSchuko, 2m H07RN-F5G2.5

### Short description for the internet:

Brennenstuhl Portable Power Distributor BSV P (2m cable, 3x 230V/16A sockets, 1x CEE 230V/16A, 1x CEE 400V/16A, construction site use and permanent outdoor use IP44, Made in Germany)

### Website short text:

Portable Power Distributor BSV P (2m cable, 3x 230V/16A sockets, 1x CEE 230V/16A, 1x CEE 400V/16A, construction site use and permanent outdoor use IP44, Made in Germany)

### Print short text:

Portable power distributor BSV P 3x 230V/16A sockets, 1x CEE 230V/16A, 1x CEE 400V/16A, 2m H07RN-F5G2.5

### Bulletpoint 1:

Power Distributor with 3 230V/16A earthed sockets, 1 230V/16A CEE socket and 1 400V/16A CEE socket with hinged covers - 5 appliances can be connected to just one power source

### Bulletpoint 2:

Multiple Distributor made of rubber for permanent outdoor use with 2m oil-resistant rubber cable H07RN-F 5G2.5

### Bulletpoint 3:

Rubber multi-way Distributor with splash-proof housing made of a special rubber compound and quality sockets to VDE 0620-1 is resistant to various oils, greases, petrol and acids, UV and ozone radiation

### Bulletpoint 4:

Robust Power Distributor - impact-resistant and resistant to ageing and weathering, with a housing for applications from -30°C to +80°C - the power distributor can be mounted flexibly thanks to the fastening strap and four screw holes

### Bulletpoint 5:

The Power Distributor with CEE 400/16A plug and ergonomically shaped carrying handle for convenient transport is characterised by its versatile range of applications in the outdoor area or on construction sites

**Online description:**

The Portable Power Distributor BSV P from Brennenstuhl with 3 earthed sockets 230V/16A, 1 CEE socket 230V/16A and 1 CEE socket 400V/16A is the ideal solution for outdoor use, e.g. on construction sites. With its splash-proof housing made of a special rubber compound and quality sockets in accordance with VDE 0620-1, the robust multiple distributor is resistant to various oils, greases, petrol and acids, UV and ozone radiation. It also has the following impressive features:

- \* Cable length: 2m
- \* Cable designation: H07RN-F 5G2.5
- \* Protection class: IP44
- \* Plug: CEE 400V/16A 5-pin/-pin
- \* 3x earthed sockets 230V/16A
- \* 1x CEE socket 230V/16A 3-pole/pin
- \* 1x CEE socket 400V/16A 5-pin/-pin
- \* Temperature resistance of the housing: -30°C to +80°C
- \* Mounting strap and four screw holes for wall mounting
- \* Max. electrical load capacity: 11,000W

**Website description:**

The Portable Power Distributor BSV P with 3 earthed sockets 230V/16A, 1 CEE socket 230V/16A and 1 CEE socket 400V/16A is the ideal solution for outdoor use, e.g. on construction sites. With its splash-proof housing made of a special rubber compound and quality sockets in accordance with VDE 0620-1, the robust multiple distributor is resistant to various oils, greases, petrol and acids, UV and ozone radiation. The robust housing is suitable for applications from -30°C to +80°C and can be flexibly mounted thanks to the fastening strap and four screw holes - for a reliable power supply wherever it is needed. It also impresses with the following features:

- \* Cable length: 2m
- \* Cable designation: H07RN-F 5G2.5
- \* Protection class: IP44
- \* Plug: CEE 400V/16A 5-pin/-pin
- \* 3x protective contact sockets 230V/16A
- \* 1x CEE socket 230V/16A 3-pole/pin
- \* 1x CEE socket 400V/16A 5-pin/-pin
- \* Max. electrical load capacity: 11,000W

**Keywords:**

power distributor, power distributor 16a, power distributor brennenstuhl, power distributor outdoor, power distributor brennenstuhl, power distributor construction site, power distributor cee, power distributor ip44, power distributor 2m

**Subtitle:**

Construction site use and permanent outdoor use, IP 44.

**Print description:**

- \* Housing made of a special rubber compound for continuous load.
- \* High-quality sockets in accordance with VDE 0620-1, resistant to various oils, greases, petrol and acids, UV radiation and ozone
- \* Robust, impact-resistant housing - resistant to ageing and weathering, can be used at temperatures from -30 °C to +80 °C.
- \* Flexible mounting thanks to mounting bracket and four screw holes.
- \* Ergonomically shaped handle for comfortable handling.
- \* CEE plug 5-pin, 400V/16A.
- \* 1x CEE socket 230V/16A 3-pin.
- \* 1x CEE socket 400V/16A 5-pole.
- \* 3 earthed sockets 230V/16A with hinged cover.

**Information text:****Table article information:****Scope of supply:**

Portable Power Distributor BSV P, Fastening strap

## Product picture 1 and 2



/publicpictures/Produktbild/1151480020.tiff

## Media



/publicpictures/Logo-Brennenstuhl/logo-made-in-germany.eps



/publicpictures/Icon/icon-special-robust-baustelle-bauhelm.eps



/publicpictures/Icon/icon-schutzart-ip44.eps

Protected against foreign bodies and splash water

\* Protection against splash water from all directions



/publicpictures/Detailansicht/1151480020-seite.tiff

/publicpictures/Detailansicht/1151480020-hinten.tiff



/publicpictures/Detailansicht/1151480020-detail-steckdosen-offen.tiff



/publicpictures/Anwendung/1151480020-anwendung-haengend-gurt.tiff



/publicpictures/Anwendung/1151480020-anwendung-mit-leiter.tiff

## Context

Attribute category:

Power distributor

Accessories:

Garantie:

Other (legal)

Spare part:

Similar products:

## Technical data

| Kabel                            |                    | Stromverteiler                                          |                             |
|----------------------------------|--------------------|---------------------------------------------------------|-----------------------------|
| Cable designation:               | H07RN-F 5G2,5      | Max. Nominal input voltage:                             | 400V                        |
| Cable assembly:                  | H07RN-F            | Type of input voltage:                                  | Alternating voltage (AC)    |
| Cable quality:                   | Rubber-Neoprene    | Type of output voltage:                                 | Alternating voltage (AC)    |
| Number of cores:                 | 5                  | Max. current carrying capacity:                         | 16A                         |
| Core cross section:              | 2.5mm <sup>2</sup> | Protection:                                             | Without                     |
| Protective conductor:            | G                  | With hinged lid/ cover:                                 | Yes                         |
| Cable length:                    | 2m                 | CEE socket - 16A:                                       | CEE 1x 16A 3P+N+E (5p) 400V |
| Cable colour:                    | black              | Number of CEE 230 V / 16A / 2P+E (3p) socket outlets:   | 1                           |
| Cable entry:                     | Bottom             | Number of CEE 400 V / 16A / 3P+N+E (5p) socket outlets: | 1                           |
| Cable entry into the housing:    | Cable gland        | Number of CEE socket outlets total:                     | 2                           |
| <b>Stromverteiler</b>            |                    | Number of earthed socket outlets:                       | 3                           |
| Type of line:                    | Connection cable   | Number of socket outlets total:                         | 5                           |
| Housing material:                | Plastic/ rubber    | Plug system socket:                                     | Type F (Protective contact) |
| Housing colour:                  | black              | With plug:                                              | Yes                         |
| Basic colour:                    | black              | Supply/ connection option:                              | Supply cable with plug      |
| With frame:                      | No                 | With CEE plug:                                          | Yes                         |
| With carrying handle:            | Yes                | Plug system plug:                                       | CEE 16A 3P+N+E (5p) 400V    |
| Material of the carrying handle: | Plastic            | <b>Mgv</b>                                              |                             |
| Military model:                  | No                 | Packaging unit (UP):                                    | 1                           |
| Packaging:                       | Without            | Weight of product (without packaging):                  | 1.78kg                      |
| Main switch:                     | Without            |                                                         |                             |
| NOT-AUS - Schalter:              | No                 |                                                         |                             |
| Suitable for suspended mounting: | No                 |                                                         |                             |
| Degree of protection (IP):       | IP44               |                                                         |                             |



|                             |         |                                          |        |
|-----------------------------|---------|------------------------------------------|--------|
| Suitable for outdoor area:  | Yes     | Length of product (without packaging):   | 12cm   |
| Protection class:           | II      | Width of product (without packaging):    | 21cm   |
| Max. electr. load capacity: | 11,000W | Height of product (without packaging):   | 43cm   |
| Nominal input voltage:      | 400V    | Weight of product (including packaging): | 1.82kg |
| Min. Nominal input voltage: | 230V    | Length of product (including packaging): | 12cm   |
|                             |         | Width of product (including packaging):  | 21cm   |
|                             |         | Height of product (including packaging): | 43cm   |

## Variant group

Portable Power Distributor BSV P CEE

- \* Housing made of a special rubber compound for continuous load.
- \* High-quality sockets in accordance with VDE 0620-1, resistant to various oils, greases, petrol and acids, UV radiation and ozone
- \* Robust, impact-resistant housing - resistant to ageing and weathering, can be used at temperatures from -30 °C to +80 °C.
- \* Flexible mounting thanks to mounting bracket and four screw holes.
- \* Ergonomically shaped handle for comfortable handling.
- \* CEE plug 5-pin, 400V/16A.
- \* 1x CEE socket 230V/16A 3-pin.
- \* 1x CEE socket 400V/16A 5-pole.
- \* 3 earthed sockets 230V/16A with hinged cover.

### Related articles

1151480020

### Variant differentiation

## Country specification

Countries/ Languages: DE\_de, RU\_ru, SE\_se, RO\_ro, NL\_nl, HU\_hu