



Pneumatic grease pump 50:1

SRL 700-25-60-kg-container

Item number: 18 713 051
EAN: 4103810424342
Discount group: D

Technical data

Length of suction tube (mm): 700
 Pressure ratio: 50:1
 Max. diameter (mm): 130
 Max. air pressure (bar): 8
 Min. air pressure (bar): 2
 Recommended air pressure (bar): 6
 Cylinder capacity engine (cm³): 220
 Cylinder capacity pump (cm³): 8
 Quantity of strokes at 8 bar at a free-flow (strokes/min): 220
 Pump capacity at 8 bar at a free-flow (g/min): 1100
 Pump pressure at 8 bar air pressure (bar): 400
 Air consumption at 8 bar air pressure (l/min): 400
 Length of discharge pipe work: depends on size of installation.
 Max. suction height: The pump is constructed to be operated directly at the point of suction
 Compressed air connection: G 1/4" female
 Grease connection, suction side (ø mm): 35
 Grease connection, pressure side: G 1/4" male
 Noise level idle running acc. to ISO 9614-2 at a distance of 2 m (db A): 78
 Noise level under load acc. to ISO 9614-2 at a distance of 2 m (db A): 77
 Viscosity of discharged liquid: grease up to NLGI 2
 Classical liquids to be discharged: lubricating greases
 Time duration for 1 complete container draining: 50 kg of grease in 50 min.
 Lacquering: blue, Pantone 294 C
 Weight (kg): 7,12
 Length of engine (mm): 225
 Weight of motor (kg): 3,400

Specification

- For 25-up to 60-kg-container
- Suction tube
- Special pump mechanism
- Pressure reducing valve (pre-set at 8 bar)
- Male quick release adapter (20 062)
- To discharge lubricating and multi purpose greases NLGI 0 up to NLGI 2

Special notes

- Pump is easy to disassemble for cleaning matters
- Operate pneumatic grease pump with maintenance unit 20 218 950, only

- 99 % emptying of the container, 1 % residual grease in the container
- Quick and simple handling with little assembly effort
- Low noise level

Packaging

Dimensions LxWxH (mm): 1000 x 180 x 180

Weight (kg): 7,7

Packing unit: 1,0