Kramp Lawn mower silicone NS02400KR

Silicone Spray is a transparent spray with lubricating and anti-adhesive characteristics based on high-grade silicone oil.

Properties:

- Lubricates
- Reduces friction and wear
- Rust and corrosion-resistant
- Water-repellent
- Electric insulating
- For in and outdoor use
- Prevents freezing and drying out of rubber parts
- Prevents rattling and squeaking of plastic parts
- Aerosol can be used in any angle (360°)

Application:

- For lubrication and protection of plastic and rubber parts
- For door rubbers, dashboards, sunroofs, sliding doors, creaking plastic parts, bumpers, rails (caravan, blinds), saw blades and cutting tools for shaping.
- Applicable in maintenance construction, vehicles / machines, agriculture and horticulture
- Both indoors and outdoors

Application method:

Surfaces must be cleaned, degreased and dry. Shake can well before use. Spray at appr. 20 cm of the object. Apply a thin layer evenly.

Technical data:

Base	Organic solvents
Consistency	Liquid
Volume organic component (VOC)	92%
Solubility in water	94,7%
Density	0,737g/ml
Propellant	Propane/Butane

Kramp Groep B.V.
Breukelaarweg 33
7051 DW Varsseveld
P.O. Box 73, 7050 AB Varsseveld
T +31 (0)315 - 254 299
F +31 (0)315 - 254 399
I www.kramp.com
IBAN BE26734044195229
SWIFT/BIC KREDBEBB
VAT NL005435511B09
KvK 09219396

Health- and Safety Recommendations:

Use only in well-ventilated areas.
In case of contact with eyes, wash immediately with plenty of water.

Packaging & logistics

Colour: transparent
Packaging: 400 ml aerosol

Shelf life:

3 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C.

Technical datasheet
Kramp Lawn mower silicone
Revision: 01-12-2024

This technical data sheet replaces al previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. It is general in nature and does not constitute any liability. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application. In every case it is recommended to carry out preliminary experiments. The manufacturer reserves the right to modify products without prior notice.

Kramp Groep B.V.
Breukelaarweg 33
7051 DW Varsseveld
P.O. Box 73, 7050 AB Varsseveld
T +31 (0)315 - 254 299
F +31 (0)315 - 254 399
I www.kramp.com
IBAN BE26734044195229
SWIFT/BIC KREDBEBB
VAT NL005435511B09
KvK 09219396