

Kramp Penetrating oil

PO02500KR

Kramp Penetrating oil is a high-quality universal spray with 8-fold action: rust dissolver, lubricant, cleaner, water-repellent, penetrating oil, corrosion resistant, contact spray and shock spray.

Properties:

- Lubricates
- Protects
- Rust and corrosion-resistant
- Reduces humidity
- Removes dirt and grease
- Cooling and shrinking effect (shockspray)
- Water-repellent
- Does not contain silicones
- For in and outdoor use
- Aerosol can be used in any angle (360°)

Application:

- To be used for machines, roller bearings, axles, cogwheels, conveyer belts, rubber gasket profiles, ...
- Is corrosion resistant. Has a penetrating action and protective film remain after cleaning.
- Does not attack rubber, plastics, or metals...

Technical data:

Base	Mixture based on mineral oil
Consistency	Liquid
Volatile Organic Compounds (VOC)	<90%
Flashpoint	<61°C
Acidity pH	Neutrale
Viscosity (20°C)	1 mPa.s
Solubility in water	Not soluble
Density	0,8 g/mL
Propellant	Propane / Butane

Application method:

Surfaces must be cleaned, degreased and dry. Shake can well before use. Spray at appr. 20 cm of the object. Apply as required. Switch electric installations back on when spray is evaporated. When used as a rust dissolver, wait for 5 to 10 minutes.

Health- and Safety Recommendations:

Use only in well-ventilated areas.

In case of contact with eyes, wash immediately with plenty of water.

Packaging & logistics

Colour: white

Packaging: 500 ml aerosol

Shelf life:

3 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C.

Technical datasheet

Kramp Penetrating oil

Revision: 30-03-2023

This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. It is general in nature and does not constitute any liability. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application. In every case it is recommended to carry out preliminary experiments. The manufacturer reserves the right to modify products without prior notice.

Kramp Groep B.V.

Breukelaarweg 33

7051 DW Varsseveld

P.O. Box 73, 7050 AB Varsseveld

T +31 (0)315 - 254 299

F +31 (0)315 - 254 399

I www.kramp.com

IBAN BE26734044195229

SWIFT/BIC KREDBEBB

VAT NL005435511B09

KvK 09219396