

Kramp Quick Start

QS02400KR

Kramp Quick Start helps the engine start instantly. And prevents excessive battery drain.

Application:

- For all types of two- and four-stroke petrol and diesel engines.
- Small engines such as outboard motors, chainsaws, lawnmowers etc.

Base	Mixture based on mineral oil and solvents
Consistence	Liquid
Volatile Organic Compounds (VOC)	99,9%
Flashpoint	<20°C
Viscosity (20°C)	1 mPa.s
Solubility in water	Insoluble
Density	0,715 g/mL
Propellant	Propane

Instructions:

Spray the starting fluid in the air filter for a few seconds and start immediately.

Gasoline engine: Accelerate gently without choking.

Diesel engine: Do not accelerate or preheat.

Packaging & shelf life

Shelf life: 3 years in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C

Packaging: 400 ml aerosol

Health and safety recommendations:

Use only in well-ventilated areas. In case of contact with eyes, wash immediately with plenty of water.

Technical datasheet

Kramp Quick Start

This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. It is general in nature and does not constitute any liability. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application. In every case it is recommended to carry out preliminary experiments. The manufacturer reserves the right to modify products without prior notice.