


User Manual

Remote Control

Ikompact Transmitter



Revision history

Table of revisions

Date	Changed	Rev
February 2019	Rebranded to Danfoss	0101

Contents

Safety instructions

General safety.....	4
Safety warnings.....	4

Technical description

Dimensions and identification.....	6
Start up.....	7

Maintenance

Maintenance tips.....	9
Troubleshooting.....	10

Safety instructions

lcompact general safety

The following safety instructions must be read carefully in order to install and use the product properly and to keep it in perfect working condition and to reduce the risk of misuse.

Potential damage to operator and product.

Do not use this product on machines in potentially explosive atmospheres unless the model is ATEX/RATEX certified to do so.

- Strictly adhere to the installation instructions contained in this document.
- Make sure that professional and competent personnel carry out the installation.
- Ensure that all site and prevailing safety regulations are fully respected.
- Make sure that this document is permanently available to the operator and maintenance personnel.
- Keep the transmission key when the set is not in use.
- On starting each working day, check to make sure that the STOP button and other safety measures are working.
- When in doubt, press the STOP button.
- Whenever several sets have been installed, make sure the transmitter is the right one. Identify the machine controlled on the label for this purpose on the transmitter or by using the display (in case it has one).
- Service the equipment periodically.
- When carrying out repairs, only use spare parts from Danfoss.

lcompact safety warnings

Potential damage to operator and product.


Follow the guidelines below to reduce risk of injury to the operator and the product.

- Use the device with the manufacturer's battery and battery charger (if applicable).
- Only allow qualified personnel to operate the equipment.
- Always set the STOP button in the off position when not in use.
- Always press STOP before plugging in tether cable (if applicable).
- Do not operate product when visibility is limited.
- Make sure product is compatible with the machine.
- Avoid knocking or dropping the product.
- Do not use the product if a failure is detected.


Changes or modifications not approved by Danfoss can void the user's authority to operate this product.

Safety instructions


Quick reference precautions




Remove the EEPROM in order to disable the transmitter




When in doubt, press the STOP button




When having the STOP button option, press it when in doubt



Make sure the transmitter works with the machine to be handled



Do not use the set when visibility is limited




Avoid knocking or dropping the set

Technical description

Ikcompact dimensions and identification

The illustration and list below describe dimensions, buttons and LEDs of the Ikcompact transmitter.

Dimensions in mm




1. Status LED
2. Feedback LEDs
3. Start push-button
4. Stop push-button
5. Stop button option
6. Attachment hook
7. Removable EEPROM module
8. Alkaline batteries module

Technical description


lcompact start up

Use the information below to properly turn the transmitter ON (OPERATION mode).

1. Place the EEPROM and the charged alkaline batteries.




2. Optional: If the transmitter has the STOP button, press and pull it out [1].



The status LED [2] will blink blue until the Stand-by mode is reached and then will turn to a constant blue [3].


3. If the transmitter does not have the STOP button, press the start button.



The status LED will blink green until the transmitter is linked with the receiver.

Technical description

4. When the receiver confirms the link, the status LED will turn into a constant green and will enter operation mode.




The transmitter is ready to be used.

Maintenance**Icompact maintenance tips**

This product is designed for use in an industrial environment that may shorten the product's lifespan. Use these tips to maximize the lifespan of the product.











- Use the hook/belt provided with the transmitter to prevent the transmitter from falling
- Do not clean the transmitter with solvents or pressurized water; use a damp cloth or soft brush for cleaning
- If the push buttons show signs of deterioration, contact the Authorized Technical Service for repair
- Check if the battery contacts are correct, otherwise replace them.
- Ensure that the product is supplied with AAA alkaline batteries or has a rechargeable battery
- Be sure to recharge or replace battery regularly

Maintenance tips quick reference

Maintenance

Ikcompact troubleshooting guide

The transmitter has status monitoring LEDs which help to identify errors and warnings. The common signals are shown in the table below.

Color and frequency	Pulse frequency	Description	Action
Blue fast pulses		System is starting; establishing connection with radio and EEPROM	Wait
Blue continuous		System is in stand-by mode, waiting for user's action	Press START to enter operation mode
Green fast pulses		Attempting to link with receiver and waiting for response	Wait
Green continuous		Working	Operate
Green slow pulses		Latency; no action has been taken for some time	Press START to return to operation mode
Red slow pulses		EEPROM module missing or corrupt	Check EEPROM and reprogram if necessary
Red double pulses		Radio communication error	Replace transmitter
Red continuous		Hardware failure	Replace transmitter
Orange slow pulses		Critical battery signal	Replace or charge batteries
Orange double pulses		Activated maneuver	Release maneuver

Products we offer:

- DCV directional control valves
- Electric converters
- Electric machines
- Electric motors
- Hydrostatic motors
- Hydrostatic pumps
- Orbital motors
- PLUS+1® controllers
- PLUS+1® displays
- PLUS+1® joysticks and pedals
- PLUS+1® operator interfaces
- PLUS+1® sensors
- PLUS+1® software
- PLUS+1® software services, support and training
- Position controls and sensors
- PVG proportional valves
- Steering components and systems
- Telematics

Danfoss Power Solutions is a global manufacturer and supplier of high-quality hydraulic and electric components. We specialize in providing state-of-the-art technology and solutions that excel in the harsh operating conditions of the mobile off-highway market as well as the marine sector. Building on our extensive applications expertise, we work closely with you to ensure exceptional performance for a broad range of applications. We help you and other customers around the world speed up system development, reduce costs and bring vehicles and vessels to market faster.

Danfoss Power Solutions – your strongest partner in mobile hydraulics and mobile electrification.

Go to www.danfoss.com for further product information.

We offer you expert worldwide support for ensuring the best possible solutions for outstanding performance. And with an extensive network of Global Service Partners, we also provide you with comprehensive global service for all of our components.

Comatrol

www.comatrol.com

Turolla

www.turollaocg.com

Hydro-Gear

www.hydro-gear.com

Daikin-Sauer-Danfoss

www.daikin-sauer-danfoss.com

Local address:

**Danfoss
Power Solutions (US) Company**
2800 East 13th Street
Ames, IA 50010, USA
Phone: +1 515 239 6000

**Danfoss
Power Solutions GmbH & Co. OHG**
Krokamp 35
D-24539 Neumünster, Germany
Phone: +49 4321 871 0

**Danfoss
Power Solutions ApS**
Nordborgvej 81
DK-6430 Nordborg, Denmark
Phone: +45 7488 2222

**Danfoss
Power Solutions Trading
(Shanghai) Co., Ltd.**
Building #22, No. 1000 Jin Hai Rd
Jin Qiao, Pudong New District
Shanghai, China 201206
Phone: +86 21 3418 5200

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequent changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.