



Protection brackets: new versions available!




101.0467, no longer available

Protection bracket Mod. 472

Order Ref. 101.0472

NEW!




for Mod. 12P and Mod. 25R



Protection bracket Mod. 473

Order Ref. 101.0473

NEW!




for Mod. 115 and Mod. 1200




Advantages:

- Simplified installation: at first the drinking bowl will be mounted in the protection bracket, then the whole unit will be mounted on the pipe with fixing brackets.
- Fixation on 2"-3½"-pipes (60-102 mm) possible
- Optimal fit for particular drinking bowl
- Reinforced construction, more stable
- During installation of a connection set for ¾" water circuits this can be secured laterally by two screws (M10x35, to be provided on site). This prevents a turning and leaks of the water circuit.





Mounting example for Mod. 12P	Mounting example for Mod. 25R
For fixation in protection bracket: 1x  100.0123 Mod. 12P-MS$\frac{3}{4}$" (alternative 100.0129 Mod. 12P-VA$\frac{3}{4}$"") 1x  101.0472 Protection bracket for Mod. 12P, 25R 6x  Hexagon screw M12x40 (alternative carriage bolt) with nut and washer (to be provided on site) For water circuit and whose fixation: 1x  103.1983 Connection set for $\frac{3}{4}$" water circuits 2x  Union for water circuits (to be provided on site) 2x  Hexagon screw M10x35 with nut (to be provided on site) For fixation of the protection bracket on pipes: 2x  Fixing brackets, suitable for the diameter of the pipe, see overview below. For heavy-duty use the protection bracket will be mounted on a plate, welded on the pipe. For Mod. 12P, see application pictures with Mod. 25R	For fixation in protection bracket: 1x  100.0253 Mod. 25R-MS$\frac{3}{4}$" (alternative 100.0259 Mod. 25R-VA$\frac{3}{4}$"") 1x  101.0472 Protection bracket for Mod. 12P, 25R 6x  Hexagon screw M12x40 (alternative carriage bolt) with nut and washer (to be provided on site) For water circuit and whose fixation: 1x  103.1983 Connection set for $\frac{3}{4}$" water circuits 2x  Union for water circuits (to be provided on site) 2x  Hexagon screw M10x35 with nut (to be provided on site) For fixation of the protection bracket on pipes: 2x  Fixing brackets, suitable for the diameter of the post, see overview below. For heavy-duty use the protection bracket will be mounted on a plate, welded on the pipe. Application pictures with Mod. 25R 

Fixing brackets for fixation on pipes



Two fixing brackets each are necessary for a protection bracket.
For heavy-duty use the protection bracket will be mounted on a plate, welded on the pipe.



Mounting example for Mod. 115	Mounting example for Mod. 1200
For fixation in protection bracket: 1x  100.0115 Mod. 115 1x  101.0473 Protection bracket for Mod. 115, 1200 4x  Hexagon screw M12x40 (alternative carriage bolt) with nut and washer (to be provided on site) For water circuit and whose fixation: Connection set for water circuits is not available. Background: e.g. on Mod. 25R the valve can be removed because the connections are integrated in the valve. Therefore the elbow can be unscrewed. On Mod. 115 the connections are tight in the cast and the connection set for water circuits can not be screwed in because the bowl is in the way. Piping to be provided on site possible as water circuit. for fixation of the protection bracket on pipes: 2x  Fixing brackets, suitable for the diameter of the pipe, see overview below. For heavy-duty use the protection bracket will be mounted on a plate, welded on the pipe.	For fixation in protection bracket: 1x  100.1203 Mod. 1200-MS$\frac{3}{4}$" (alternative 100.1209 Mod. 1200-VA$\frac{3}{4}$"") 1x  101.0473 Protection bracket for Mod. 115, 1200 4x  Hexagon screw M12x40 (alternative carriage bolt) with nut and washer (to be provided on site) For water circuit and whose fixation: 1x  103.1983 Connection set for $\frac{3}{4}$" water circuits (only for downwards connection) 2x  Union for water circuits (to be provided on site) 2x  Hexagon screw M10x35 with nut (to be provided on site) For fixation of the protection bracket on pipes: 2x  Fixing brackets, suitable for the diameter of the pipe, see overview below. For heavy-duty use the protection bracket will be mounted on a plate, welded on the pipe. Application pictures with Mod. 1200: 

Fixing brackets for fixation on pipes

2" (60 mm)

131.0169



2½" (77 mm)

101.1241



3½" (102 mm)

101.1242



Two fixing brackets each are necessary for a protection bracket.
For heavy-duty use the protection bracket will be mounted on a plate, welded on the pipe.