


Nozzles



TurboDrop® TD-XL Standard

Universal venturi flat fan nozzle
with integrated standard bayonet cap
– all plastic or semi ceramic

Sizes	Recom- mended strainer	Order no. Semi ceramic	Order no. Plastic
110-01	100 M green	13605	13666
110-015	50 M blue	13656	13665
110-02	50 M blue	13658	13668
110-025	50 M blue	13657	13667
110-03	50 M blue	13659	13669
110-04	50 M blue	13660	13670
110-05	50 M blue	13661	13671
110-06	24 M red	13662	13672
110-08	24 M red	13663	13673
110-10	24 M red	13664	13674
110-15	–	–	16111

Specifications	
 Spray angle 110°	 Optimum spray height 40 – 60 cm
 Pressure range 1 – 8 bar	
Optimum pressure Pesticides: 2 – 4 bar Liquid fertilizer: 1 – 2 bar	Typical application 



Features

- Produces a variable and low-drift droplet spectrum and finer droplets at high pressures
- Very large range of setting options
- Two-piece design with TCP distributor tip for very easy cleaning without tools
- The distributor tip is exactly twice the size of the venturi
- Venturi and distributor tip have different ISO colours

- Ideal for mixed arable farms where water volumes and droplet sizes vary depending on the application
- Extremely wear-resistant, especially in semi ceramic specification

For litre/ha rates, see the ISO tables on pages 62/67.

For flow rates, see the table on page 66.

For application rate formulas, see page 71.

Supplied with standard 3mm sealing ring (charged extra).