



AIC TeeJet® Air Induction Flat Spray Tips

Typical Applications:

See selection guide on pages 2 and 6 for recommended typical applications for AIC TeeJet tips.

Features:

- Produces a 110° tapered edge flat spray pattern for uniform coverage in broadcast spraying applications.
- Available with a polymer insert holder with stainless steel (015–10 capacities), ceramic (025–05 capacities) or polymer (02–05 capacities) inserts.

- Larger droplets for less drift.
- Depending on the chemical, produces large air-filled drops through the use of a Venturi air aspirator.
- AI TeeJet nozzle molded into Quick TeeJet® cap provides automatic spray alignment.
- Includes tightly fitting washer that stays put and assures a good seal.
- Recommended pressure rating 30–115 PSI (2–8 bar).




Note: Due to the pre-orifice design, this tip is not compatible with the 4193A check valve tip strainer.

Tip No.	Capacity One Nozzle IN /min	Drop Size	CAPACITY ONE NOZZLE IN /min	l/ha \triangle 50cm \triangle													
				4 km/h	5 km/h	6 km/h	7 km/h	8 km/h	10 km/h	12 km/h	16 km/h	18 km/h	20 km/h	25 km/h	30 km/h	35 km/h	
AIC110015 (100)	VC	2.0	0.48	144	115	96.0	82.3	72.0	57.6	48.0	36.0	32.0	28.8	23.0	19.2	16.5	
	VC	3.0	0.59	177	142	118	101	88.5	70.8	59.0	44.3	39.3	35.4	28.3	23.6	20.2	
	C	4.0	0.68	204	163	136	117	102	81.6	68.0	51.0	45.3	40.8	32.6	27.2	23.3	
	C	5.0	0.76	228	182	152	130	114	91.2	76.0	57.0	50.7	45.6	36.5	30.4	26.1	
	C	6.0	0.83	249	199	166	142	125	99.6	83.0	62.3	55.3	49.8	39.8	33.2	28.5	
	C	7.0	0.90	270	216	180	154	135	108	90.0	67.5	60.0	54.0	43.2	36.0	30.9	
AIC11002 (50)	VC	2.0	0.65	195	156	130	111	97.5	78.0	65.0	48.8	43.3	39.0	31.2	26.0	22.3	
	VC	3.0	0.79	237	190	158	135	119	94.8	79.0	59.3	52.7	47.4	37.9	31.6	27.1	
	VC	4.0	0.91	273	218	182	156	137	109	91.0	68.3	60.7	54.6	43.7	36.4	31.2	
	C	5.0	1.02	306	245	204	175	153	122	102	76.5	68.0	61.2	49.0	40.8	35.0	
	C	6.0	1.12	336	269	224	192	168	134	112	84.0	74.7	67.2	53.8	44.8	38.4	
	C	7.0	1.21	363	290	242	207	182	145	121	90.8	80.7	72.6	58.1	48.4	41.5	
AIC110025 (50)	XC	2.0	0.81	243	194	162	139	122	97.2	81.0	60.8	54.0	48.6	38.9	32.4	27.8	
	VC	3.0	0.99	297	238	198	170	149	119	99.0	74.3	66.0	59.4	47.5	39.6	33.9	
	VC	4.0	1.14	342	274	228	195	171	137	114	85.5	76.0	68.4	54.7	45.6	39.1	
	VC	5.0	1.28	384	307	256	219	192	154	128	96.0	85.3	76.8	61.4	51.2	43.9	
	C	6.0	1.40	420	336	280	240	210	168	140	105	93.3	84.0	67.2	56.0	48.0	
	C	7.0	1.51	453	362	302	259	227	181	151	113	101	90.6	72.5	60.4	51.8	
AIC11003 (50)	XC	2.0	0.96	288	230	192	165	144	115	96.0	72.0	64.0	57.6	46.1	38.4	32.9	
	VC	3.0	1.18	354	283	236	202	177	142	118	88.5	78.7	70.8	56.6	47.2	40.5	
	VC	4.0	1.36	408	326	272	233	204	163	136	102	90.7	81.6	65.3	54.4	46.6	
	VC	5.0	1.52	456	365	304	261	228	182	152	114	101	91.2	73.0	60.8	52.1	
	C	6.0	1.67	501	401	334	286	251	200	167	125	111	100	80.2	66.8	57.3	
	C	7.0	1.80	540	432	360	309	270	216	180	135	120	108	86.4	72.0	61.7	
AIC11004 (50)	XC	2.0	1.29	387	310	258	221	194	155	129	96.8	86.0	77.4	61.9	51.6	44.2	
	VC	3.0	1.58	474	379	316	271	237	190	158	119	105	94.8	75.8	63.2	54.2	
	VC	4.0	1.82	546	437	364	312	273	218	182	137	121	109	87.4	72.8	62.4	
	VC	5.0	2.04	612	490	408	350	306	245	204	153	136	122	97.9	81.6	69.9	
	VC	6.0	2.23	669	535	446	382	335	268	223	167	149	134	107	89.2	76.5	
	C	7.0	2.41	723	578	482	413	362	289	241	181	161	145	116	96.4	82.6	
AIC11005 (50)	C	8.0	2.58	774	619	516	442	387	310	258	194	172	155	124	103	88.5	
	XC	2.0	1.61	483	386	322	276	242	193	161	121	107	96.6	77.3	64.4	55.2	
	XC	3.0	1.97	591	473	394	338	296	236	197	148	131	118	94.6	78.8	67.5	
	VC	4.0	2.27	681	545	454	389	341	272	227	170	151	136	109	90.8	77.8	
	VC	5.0	2.54	762	610	508	435	381	305	254	191	169	152	122	102	87.1	
	VC	6.0	2.79	837	670	558	478	419	335	279	209	186	167	134	112	95.7	
AIC11006 (50)	C	7.0	3.01	903	722	602	516	452	361	301	226	201	181	144	120	103	
	C	8.0	3.22	966	773	644	552	483	386	322	242	215	193	155	129	110	
	XC	2.0	1.94	582	466	388	333	291	233	194	146	129	116	93.1	77.6	66.5	
	XC	3.0	2.37	711	569	474	406	356	284	237	178	158	142	114	94.8	81.3	
	VC	4.0	2.74	822	658	548	470	411	329	274	206	183	164	132	110	93.9	
	VC	5.0	3.06	918	734	612	525	459	367	306	230	204	184	147	122	105	
AIC11008 (50)	VC	6.0	3.35	1005	804	670	574	503	402	335	251	223	201	161	134	115	
	C	7.0	3.62	1086	869	724	621	543	434	362	272	241	217	174	145	124	
	C	8.0	3.87	1161	929	774	663	581	464	387	290	258	232	186	155	133	
	XC	2.0	2.58	774	619	516	442	387	310	258	194	172	155	124	103	88.5	
	XC	3.0	3.16	948	758	632	542	474	379	316	237	211	190	152	126	108	
	VC	4.0	3.65	1095	876	730	626	548	438	365	274	243	219	175	146	125	
AIC11010	VC	5.0	4.08	1224	979	816	699	612	490	408	306	272	245	196	163	140	
	VC	6.0	4.47	1341	1073	894	766	671	536	447	335	298	268	215	179	153	
	C	7.0	4.83	1449	1159	966	828	725	580	483	362	322	290	232	193	166	
	C	8.0	5.16	1548	1238	1032	885	774	619	516	387	344	310	248	206	177	
	XC	2.0	3.23	969	775	646	554	485	388	323	242	215	194	155	129	111	
	XC	3.0	3.95	1185	948	790	677	593	474	395	296	263	237	190	158	135	
AIC11010	VC	4.0	4.56	1368	1094	912	782	684	547	456	342	304	274	219	182	156	
	VC	5.0	5.10	1530	1224	1020	874	765	612	510	383	340	306	245	204	175	
	VC	6.0	5.59	1677	1342	1118	958	839	671	559	419	373	335	268	224	192	
	VC	7.0	6.03	1809	1447	1206	1034	905	724	603	452	402	362	289	241	207	
	C	8.0	6.45	1935	1548	1290	1106	968	774	645	484	430	387	310	258	221	


Note: Always double check your application rates. Tabulations are based on spraying water at 70°F (21°C).



CONTACT PRODUCT	SYSTEMIC PRODUCT	DRIFT MANAGEMENT
GOOD	EXCELLENT	EXCELLENT



Optimum Spray Height



See pages 173–187 for drop size classification, useful formulas and information.

How to order:

Specify tip number.

- Examples:
- AIC11004-VS – Stainless Steel with VisiFlo® color-coding
 - AIC11003-VP – Polymer with VisiFlo color-coding
 - AIC11003-VK – Ceramic with VisiFlo color-coding