example: VX 186-260 Q S6 H 4 O 2 VVA AT 1 model RP = Profi pump V pump with seal chamber V I
IQ = pump with IQ-service VX = pump with big R = pump without seal chamber seal chamber
2 pump type shaft centre distance - chamber length
3 version Q = QuickService HD = pump with mechanical seal QD = QuickService (on both sides in the o-ring) with additional bearing []+L = pump with reduced starting torque QG = QuickService gearbox side []
4 shafts S6 = PTO-shaft (DIN 9611 model 1; 6-parts 1 ³ / _a ") S21 = PTO-shaft (DIN 9611 model 2; 21-parts 1 ³ / _a ") P6 = PTO-shaft (non-standardized, 6-parts 1 ³ / _a ") P20 = PTO-shaft (DIN 9611 model 3; 20-parts 1 ³ / _a ") MU = bottom keyed shaft MHU = bottom keyed shaft MHO = top hydraulik motor shaft []+T = TopService * shaft combinations, which are not described above, are marked separately Each single shaft of the pump is marked "U" means bottom shaft "O" means top shaft "K" means Combi-pump with shafts on both ends of the pump examples: OS6 / US6 / KOS6 or OP6 / US6. * "X" means shrinked shaft end, for example SX6
5 rotary lobe geometry H = HiFlo® G = two-wing K = HiFlo®, enlarged rubber layer F = two-wing, enlarged rubber layer HP = HiFlo® <i>plus</i> GW = two-wing, changing lobe tips, steel core GW = two-wing, changing lobe tips, steel core GW = two-wing, changing lobe tips, steel core HWE = HiFlo, changing lobe tips, stainless steel core HWE = HiFlo, changing lobe tips, stainless steel core
6 rotary lobe material / elastomers 2 = NBR 8 = PUR 14 = EPDM-AL (aqua line) 3 = NBR white 9 = EPDM white 19 = stainless steel 4 = EPDM 10 = HNBR 20 = POM 5 = FPM 11 = CSM 21 = steel 6 = SBR 12 = EPDM-SL (sewage line) 7 = WEROBUST 13 = FPM blue
7 separation plate [] = without distance plate M = Marathon + number of chambers O = suction side and discharge side open D = DuoShift L = closed on the left side R = closed on the right side (view from the non-drive end) G = closed on both sides G = closed on both sides
8 pump chamber(s) [] = only one pump chamber quantity or width of each single pump chamber: * if pump chambers are equal, only quantity of chambers * "X" for unequal pump chambers, each width in mm mentioned at the bottom of the nameplate, beginning at the non-drive end * For Marathon each chambers are added to overall length * axial labyrinth-sealings are mentioned as a separate chamber
Pump chamber lining [] = housing segments out of grey cast iron, wear plates and separation plates out of Hardox VVA = housing segments out of cast SS 316, mech. seal, wear plates and separation plates out of SS 316, wear plates with enlarged thickness
10 elastomer nomination of the sealings
E + [] 6 = FKM / FEPM 2 = NBR / HNBR 8 = EPDM / MVQ (Silicone) 4 = EPDM 10 = MVQ (Silicone), FEP coated / FFKM (Perlast®) 5 = FKM 14 = MVQ (Silikon), FEP coated / FEPM (Fluoraz®)
11 status [] = new pump AT = reconditioned pump