

Design


The Hallite 831 wiper is designed to snap into a standard housing and provide reliable medium duty dirt exclusion. The proportions of the precision trimmed wiping lip ensure that it remains in contact with the rod surface to remove all deposits of mud and other forms of contamination except for those found in heavy duty industrial applications.

The outside diameter of the seal incorporates a 'crush lip' to provide interference fit with the housing and a 'face bead' to ensure that the crush lip is not trapped in the corner of the housing. The inside diameter of the seal is provided with ribs to prevent the possibility of blow-out due to pressure trapping of the main rod seal.

The Hallite 831 is precision moulded in polyurethane for maximum wear resistance and is interchangeable with many common European wiper styles.

Features

- Precision trimmed sealing lip
- 'Crush Lip' and 'Face Bead' provide effective seal on housing
- Low wear
- Long life
- Cost effective
- Pressure relief ribs



Technical details

Operating conditions

	Metric	Inch
Maximum Speed	4.0 m/sec	12.0 ft/sec
Temperature Range	-45°C +110°C	-50°F +230°F

Surface roughness

	µmRa	µmRt	µinCLA	µinRMS
Dynamic Sealing Face ØD ₁	0.1 < > 0.4	4 max	4 < > 16	5 < > 18
Static Sealing Face Ød ₁	1.6 max	10 max	63 max	70 max
Static Housing Faces L ₁	3.2 max	16 max	125 max	140 max

Radii

Rod Diameter Ød ₁	≤ 90	> 90
Max Fillet Rad r ₁ mm	0.2	0.4
Max Fillet Rad r ₂ mm	0.4	0.4

Tolerances

mm	Ød ₁ f9	ØD ₁ H11	ØD ₂ H11	L ₁ +0.2 -0
----	-----------------------	------------------------	------------------------	---------------------------

