













# 3M™ Duct, Cloth & Sealing Tapes



**Built to stick**

Product	Number	Properties/ Suitable for	Indoor/ Outdoor use	Key Features
	1900	Value duct tape		<ul style="list-style-type: none"> <li>Noncritical light-duty sealing and holding applications</li> </ul>
	2903	General purpose		<ul style="list-style-type: none"> <li>General maintenance, bundling, wrapping, attaching, sealing, and protecting</li> </ul>
	389	Professional grade		<ul style="list-style-type: none"> <li>Heavy duty industrial and MRO applications</li> <li>Colour marking</li> </ul>
	8979	Clean removal	 	<ul style="list-style-type: none"> <li>Heavy duty industrial and MRO applications</li> <li>Removes cleanly from most opaque surfaces for up to 6 months</li> </ul>
	4411	Extreme sealing	 	<ul style="list-style-type: none"> <li>Sealing applications like joints, seams, penetration, roof top, roof-to-trim, skylight</li> <li>Conforms over contours, edges, rivets and screw heads for a water tight seal</li> </ul>

**Product Use**

All statements, technical information, and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law.