

			Bosch equivalent	Total length	Toothed length	Height	Thickness	Pitch		Material	Stainless steel	Metals	Sheet metals	Perf. sheet metal		Profiles	Metal pipes	Thin pipes	Non-ferrous metals	Aluminium	Steel pipes, cast pipes	Fibre materials	GFK/FRP	PVC / plastic materials	Plastic profiles	Wood with steel elements	Wood with hardened screws / nails	Pallets	Wood with nails	Solid wood	Chipboard	Sandwich materials / cement bonded chipboard	Metal stud	
	Type	Item		mm	mm	mm	mm	mm	TPI																									
Inox	RCM30B	752043	---	150,0	128,5	19,0	0,90	1,8	14	BiM	•	•												o										
	RCM40B	752044	---	200,0	178,5	19,0	0,90	1,8	14	BiM	•	•												o										
	RCM50B	752045	---	250,0	228,5	19,0	0,90	1,8	14	BiM	•	•												o										
	RS10	752035	S518EHM	115,0	93,5	19,0	1,25	1,4	18	HM/TC	•	o									•													
Metal	RCM31B	752676	---	150,0	128,5	19,0	0,90	1,8	14	BiM		•	o			•	•			o														
	RCM41B	752677	---	225,0	203,5	19,0	0,90	1,8	14	BiM		•	o			•	•			o														
	RCM32B	752678	---	150,0	128,5	19,0	0,90	1,8-2,6	10-14	BiM		•	o			•	•			o														
	RCM42B	752679	---	225,0	203,5	19,0	090	1,8-2,6	10-14	BiM		•	o			•	•			o														
	RM39B	752681	S921CHF	150,0	128,5	25,0	1,10	2,5-3,0	8-10	BiM		•		•		•				o				o					o					
	RM49B	752682	S1121CHF	225,0	203,5	25,0	1,10	2,5-3,0	8-10	BiM		•				•				o				o					o					
	RM38B	752683	S921BEF	150,0	128,5	25,0	1,10	1,4-1,8	14-18	BiM		•	o				o	•		o														
	RM48B	752684	S1121BEF	225,0	203,5	25,0	1,10	1,4-1,8	14-18	BiM		•	o				o	•		o														
	RM44B	752021	S1120CF	225,0	203,5	22,0	1,60	2,5-3,0	8-10	BiM		•		•		•				o									o					
	RM37B	752020	S920CF	150,0	128,5	22,0	1,60	2,5-3,0	8-10	BiM		o		•		•				•									o					
	RM50B	752019	S1025VF	200,0	178,5	19,0	1,25	1,8-2,6	10-14	BiM		•	o	•		•				o														
	RPM30B	752018	S123XF	150,0	128,5	19,0	0,90	Progress.	8-14	BiM		•	o	•			o		•	•			o		o					o				
	RM43B	752017	S1122BF	225,0	203,5	19,0	0,90	1,8	14	BiM		•	o				•		•	o	o		o											
	RM36B	752016	S922BF	150,0	128,5	19,0	0,90	1,8	14	BiM		•	•				o		•	o	o		o											
	RM42B	752014	S1122EF	225,0	203,5	19,0	0,90	1,4	18	BiM		•	•				o			o														
	RM34B	752012	S922AF	150,0	128,5	19,0	0,90	1,0	24	BiM		•	•				o				o													
RM11B	752015	S422BF	100,0	78,5	8,0	0,90	1,8	14	BiM		•							•	o			o												
Wood + metal	RPD33B	752685	S956XHM	150,0	128,5	25,0	1,25	Progress.	6-8	HM/TC										•			•			•	•							
	RPD43B	752686	S1156XHM	225,0	203,5	25,0	1,25	Progress.	6-8	HM/TC										•			•			•	•						o	
	RW50B	752027	S1411DF	305,0	283,5	19,0	1,25	4,0	6	BiM													•					•	•	•	o		o	
	RD50B	752028	S1110DF	225,0	203,5	22,0	1,60	4,0	6	BiM		o																•	•	•				
	RD31B	752025	S611DF	150,0	128,5	19,0	1,25	4,0	6	BiM												o		•	•		•	•	•	o				
	RD32B	752026	S711DF	150,0	128,5	12,0	1,25	4,0	6	BiM												o		•			•	o	o	o	o			
	RPD40B	752024	S3456XF	200,0	178,5	19,0	1,25	Progress.	6-12	BiM		•										o		o				•	o	o	•			
	RD70B	752023	S1222VF	305,0	283,5	19,0	0,90	1,8-2,6	10-14	BiM		•				•			o	o	o		o		o			o			•			
	RD30B	752022	S922VF	150,0	128,5	19,0	0,90	1,8-2,6	10-14	BiM		•	o			•				o			o		o			o			o			
RD40B	752048	S1122HF	225,0	203,5	19,0	0,90	2,5	10	BiM																	•	•	o	o					
			Bosch equivalent	Dimensions																														
	Type	Item		mm	mm	mm	mm	mm	TPI																									
Wood	RPW80	752033	S2345X	200,0	178,5	19,0	1,25	Progress.	6-10	HCS			o			•	•			•														
	RW30	752032	S1531L	240,0	218,5	19,0	1,50	5,0	5	HCS						o			•															
	RW70	752031	S1344D	305,0	283,5	19,0	1,25	4,0	6	HCS						•	o	o																
	RW10	752030	S644D	150,0	128,5	19,0	1,25	4,0	6	HCS						•	o																	
	RW60	752029	S1111K	225,0	203,5	19,0	1,25	8,5	3	HCS						o			•															
	Masonry	RB50	752040	S1543HM	240,0	193,5	22,0	1,50	12,7	2	HM/TC										•	•												
RB70		752041	S1243HM	305,0	283,5	50,0	1,50	12,7	2	HM/TC										•	•													
RB90		752042	S2243HM	457,0	432,2	50,0	1,50	12,7	2	HM/TC										•	•													
Special	RC10	752039	S1130RIFF	225,0	203,5	19,0	1,25	Gritted Grain 30	HM/TC	•		o													o	o	o	o						
	RW20	752034	S828D	150,0	128,5	19,0	1,00	4,0	6	HAS													•			•								
	RP10	752675	-	100,0	78,5	19,0	1,05	4,0	6	HCS			•			o	o	o																
	RS72	752687	S1211K	305,0	283,5	19,0	1,25	8,5	3	INOX						o															•	•		
	RS70	752037	S1241HM	305,0	283,5	22,0	1,50	8,5	3	HM/TC		•	•								o		o	•	o	o	o							
	RS80	752038	S2041HM	400,0	378,5	22,0	1,50	12,7	2	HM/TC		•	•								o		o	•	o	o	o							
	RS74	752688	S1213AWP	305,0	283,5	22,0	1,50	Serrated Knife	HCS																			•	•	o	o			
	RS84	752689	S2013AWP	400,0	378,5	45,0	1,50	Serrated Knife	HCS																			•	•	o	o			